

RECON Traction Drive Scrubber

RECON 20" / 150-20TD

GENERAL

Machine shall be of the type generally described as a battery-powered "automatic":

The specific model and size should be:

This bid defines a self-propelled machine that wet "scrubs and dry" vacuums a path of:

For expedited parts delivery, machine shall be made in:

The machine contains separate tanks for solution and recovery water, with a minimum capacity in each tank of:

Tomcat

RECON 20-D

20"

United States

10 gallons

SOLUTION TANK

The solution tank shall be made of heavy gage (.3125") polyethylene plastic. Dual fill ports, with one at the front of the machine and a second at the rear. Solution screen must be stainless steel and located, with the check valve, on the scrub deck permitting top access. The solution tank specifically must hold a minimum of:

10 gallons

RECOVERY TANK

Recovery tank shall be made of polyethylene, that is a minimum thickness of (.3125"). Tank shall be designed to be easy to clean, with complete access to the recovery tank's floor, wherein the entire inside and floor of the tank is visible and reachable. A heavy duty, discharge control, 1.5" diameter drain hose shall be supplied, made of latex rubber. To simplify access for planned maintenance, tank must include:

"Tip Back" feature

Recovery tank must include "Drain Saver" basket, to collect all liter in the recovery water, to keep discharge water from clogging floor drains. Drain saver basket must be constructed of stainless steel, with 1/4" mesh screen, and be removed without tools or loose fasteners. Tank Capacity of:

10 gallons

BRUSHES/PADS

For preferred maneuverability and productivity the machine shall use:

Scrub brushes/pads shall be:

For preferred cleaning performance the machine's scrub brushes/pads should operate at:

1 Disk Brush

(1x) 20"

200 rpm

BRUSH HEAD

To reduce the stress on the operator, the machine's brush head shall be raised and lowered by an electric actuator with a minimum capacity of:

125 lbs

BRUSH MOTOR

The scrub motor shall be heavy duty, permanent-magnet DC:

(1x) .75 hp / 200 rpm

VACUUM MOTOR

The vacuum motor is to be protected with a ball and stainless screen system wherein the ball reacts to the level of foam inside the tank and shuts off air flow to the vacuum motor. The vacuum motor must be 3-stage and rated at:

3-Stage / 0.8 hp - 640 watts

SQUEEGEE

Squeegee shall move when the machine turns to control water. It shall be protected against impact with "Non-Marking" 4" diameter, side wheels, and a breakaway feature. For preferred water recovery, the squeegee shall have a minimum width of:

30"

To reduce potential recovery water discharge back onto the floor when squeegee is raised, the Squeegee Hose shall have a Pig Tail Trap.

Standard

DRIVE SYSTEM

Shall be equipped with a drive motor of:

0.35 hp

For preferred stability and traction, unit shall be propelled by:

All-Gear Sealed Transaxle

TIRES / CASTERS

For preferred machine maneuverability, only machines with a 3-point stance will be acceptable. Machines with 4-point stance will not be considered.
Front casters shall be solid, non-marking and size minimum of:
Rear caster wheels shall be solid, low rolling resistant, non-marking and size minimum of:

4-Point Stance
(2x) 2.5" dia x 1.5" wide
(2x) 8" dia x 2" wide

BATTERIES

Scrubber shall include at least 2 batteries, to form a minimum of 24-volt DC system. Batteries must be located in a 7" tall, plastic battery tray to contain any and all fluids. The battery size must be a minimum of:

For extended run time, optional battery/charger upgrade should be quoted in the size of:
Battery brand must be:

85 ah
130 ah / 12 amp
Trojan

CHARGER

Charger shall be "shelf mounted", and fully automatic type, running on 110-volt / 60-Hz / AC power. It shall provide a minimum of 24-volt DC output of:

8 amps

CONTROLS

A button control system shall be situated within the metal handlebar, arranged to allow operator to engage forward speed with the fingers of either hand. For operator ease and more stable control, the speed control must be a separate control. Twist grip controls which govern direction change along with speed, will not be considered.

The squeegee shall be lifted and lowered by a simple lever, with the vacuum operating whenever the switch is engaged. To more completely dry the squeegee hose, and reduce discharge back onto the floor, the hose shall have a:

Trap

DIMENSIONS

Machine maximum dimensions shall be:
Machines maximum weight (including batteries) shall be:

(35"L x 18"W x 38"H)
290 - 340 lbs

CONSTRUCTION

For preferred durability and longevity the scrubber's main frame shall be made of a steel, powder-painted to resist corrosion, and of a thickness of at least:
This heavy gage frame shall fully support the weight of the batteries, the tanks, hold the scrub deck rigid and locate the casters and transaxle. For future ease of service, all of the fasteners on the scrubber shall be made of:

10-gage (1/8")
Stainless Steel

No machine with casters or transaxle mounts that bolt directly to the tanks will be acceptable.

OTHER FEATURES / OPTIONS

Non-Marking Tires
Solid HD Tires (P7 Rubber / Black)
E-Stop
Remote Spray Hose
Vacuum Wand
Sealed Batteries
Onboard Charger
Stainless Steel Baffle
Stainless Steel Scrub Deck
Parking Brake

Standard
Optional
Optional
Optional
Optional
Optional
Standard
Optional
Optional